


**DESCRIPTION**

KPESD5V0C1BL is a low-capacitance Transient Voltage Suppressor (TVS) designed to provide electrostatic discharge (ESD) protection for data, control or power lines. With typical capacitance of 10pF only, is designed to protect parasitic-sensitive systems against over-voltage and over-current transient events. It complies with IEC 61000-4-2 (ESD), Level 4 ( $\pm 15\text{kV}$  air,  $\pm 8\text{kV}$  contact discharge), IEC 61000-4-4 (electrical fast transient - EFT) (40A, 5/50 ns), very fast charged device model (CDM) ESD and cable discharge event (CDE), etc.

The KPESD5V0C1BL uses ultra-small DFN1006 package. Each device can protect one data line. It offers system designers flexibility to protect single data line where space is a premium concern.

**ORDERING INFORMATION**

- ✧ Package: DFN1006
- ✧ Marking: FOC
- ✧ Material: RoHS compliant, Halogen free
- ✧ Packing: Tape & Reel
- ✧ Quantity per reel: 10,000pcs

**CIRCUIT DIAGRAM****FEATURES**

- ✧ Transient protection for high-speed data lines  
IEC 61000-4-2 (ESD)  $\pm 15\text{kV}$  (Air)  
 $\pm 8\text{kV}$  (Contact)  
IEC 61000-4-4 (EFT) 40A (5/50 ns)  
Cable Discharge Event (CDE)
- ✧ Package optimized for high-speed lines
- ✧ Ultra-small package (1.0mm $\times$ 0.6mm $\times$ 0.4mm)
- ✧ Protects one data, control or power line
- ✧ Low capacitance
- ✧ Low leakage current
- ✧ Low clamping voltage
- ✧ Each I/O pin can withstand over 1000 ESD strikes for  $\pm 8\text{kV}$  contact discharge

**MACHANICAL DATA**

- ✧ DFN1006 package
- ✧ Flammability Rating: UL 94V-0
- ✧ Packaging: Tape and Reel
- ✧ High temperature soldering guaranteed: 260°C/10s
- ✧ Reel size: 7 inch
- ✧ MSL3

**APPLICATIONS**

- ✧ Portable Electronics
- ✧ Desktops, Servers and Notebooks
- ✧ Cellular Phones
- ✧ MP3 Ports
- ✧ Digital Ports
- ✧ Subscriber Identity Module (SIM) card

**PIN CONFIGURATION**


**ABSOLUTE MAXIMUM RATING**

| Symbol    | Parameter  | Value                | Units       |
|-----------|--|----------------------|-------------|
| $V_{ESD}$ | ESD per IEC 61000-4-2 (Air)<br>ESD per IEC 61000-4-2 (Contact) | $\pm 30$<br>$\pm 30$ | kV          |
| $P_{PP}$  | Peak Pulse Power (8/20 $\mu$ s)                                | 150                  | W           |
| $T_{OPT}$ | Operating Temperature  | -40~150              | $^{\circ}C$ |
| $T_{STG}$ | Storage Temperature  | -40~150              | $^{\circ}C$ |


**ELECTRICAL CHARACTERISTICS ( $T_{amb}=25^{\circ}C$ )**

| Symbol    | Parameter                 | Test Condition                      | Min | Typ | Max  | Units   |
|-----------|---------------------------|-------------------------------------|-----|-----|------|---------|
| $V_{RWM}$ | Reverse Working Voltage   |                                     |     |     | 5.0  | V       |
| $V_{BR}$  | Reverse Breakdown Voltage | $I_T = 1mA$                         | 5.6 |     | 7.8  | V       |
| $I_R$     | Reverse Leakage Current   | $V_{RWM} = 5V$                      |     |     | 1.0  | $\mu A$ |
| $V_C$     | Clamping Voltage          | $I_{PP} = 5A, t_p = 8/20\mu s$      |     |     | 11.6 | V       |
| $V_C$     | Clamping Voltage          | $I_{PPmax} = 9.4A, t_p = 8/20\mu s$ |     |     | 16.0 | V       |
| $C_J$     | Junction Capacitance      | $V_R = 0V, f = 1MHz$                |     | 10  | 15   | pF      |

**ELECTRICAL CHARACTERISTICS CURVE**




**Pulse Waveform**




**Power Derating Curve**

**DFN1006 PACKAGE OUTLINE DIMENSIONS**



Unit: mm

|    | MIN     | NOM  | MAX  |
|----|---------|------|------|
| D  | 0.55    | 0.60 | 0.65 |
| E  | 0.95    | 1.00 | 1.05 |
| L1 | 0.20    | 0.25 | 0.30 |
| L2 | 0.20    | 0.25 | 0.30 |
| b  | 0.45    | 0.50 | 0.55 |
| e  | 0.65BSC |      |      |
| A  | 0.45    | 0.50 | 0.55 |
| h  | 0.07    | 0.12 | 0.17 |



**Soldering Footprint**